

Cabot's Stain & Varnish Water Based Gloss

AUDW1634

Part A	538-line
--------	----------

Description

Cabot's Stain & Varnish Water Based is a combined stain and clear varnish in one for all interior timber. It's easy to apply and is highly durable, resisting scuffing and scratching. As it's water based, it is fast drying so you can recoat after only 2 hours and clean up is easy with water.

Features

- Resists stains & scratches.
- Enhances timber grain.
- Fast recoat.
- Low odour.
- No topcoat required.

Benefits

- Forms a durable protective finish which resists scuffing, scratching and household wear & tear.
- Enhances rather than hides the natural timber grain.
- Recoat after only 2 hours.
- Virtually no odour.
- Stain and durable clear finish all in one, meaning no top coat is required.

Uses




All bare interior timber.

Precautions And Limitations

Do not apply this product if the temperature is below 10°C or above 35°C.

Performance Guide

Weather	Interior use only.	Salt	Unaffected by splash or spillage.
Water	Good water resistance.	Solvent	Resists alcohols and hydrocarbons.
Abrasion	Resists scuffing, scratching and household wear & tear.	Acid	Suitable for dilute splash.
Alkali	Suitable for dilute splash.		

Typical Properties																											
Gloss Level	Gloss	Components	1																								
Number Of Coats	3	V.O.C. Level	< 15g/L																								
Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinters required for non-factory packaged colours.	Touch Dry	30 Minutes																								
Clean Up	 Water																										
Application Method	 Brush  Roller																										
Application Conditions	<table> <tr> <td>Solids By Volume</td><td>26</td><td></td><td></td></tr> <tr> <td></td><td>Min</td><td>Max</td><td>Recommended</td></tr> <tr> <td>Wet Film Per Coat (microns)</td><td></td><td></td><td>62</td></tr> <tr> <td>Dry Film Per Coat (microns)</td><td></td><td></td><td>16</td></tr> <tr> <td>Recoat Time (min)</td><td>2 Hours</td><td></td><td></td></tr> <tr> <td>Theoretical Spread Rate (m²/L)</td><td></td><td></td><td>16</td></tr> </table>			Solids By Volume	26				Min	Max	Recommended	Wet Film Per Coat (microns)			62	Dry Film Per Coat (microns)			16	Recoat Time (min)	2 Hours			Theoretical Spread Rate (m²/L)			16
Solids By Volume	26																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			62																								
Dry Film Per Coat (microns)			16																								
Recoat Time (min)	2 Hours																										
Theoretical Spread Rate (m²/L)			16																								
Typical Properties Notes	<p>SPREADING RATE Up to 16 square metres per litre depending on the porosity and condition of the timber.</p> <p>DRYING AND RECOAT TIME All timings quoted at 25C and 50% humidity. Cooler or humid conditions may require longer.</p>																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> Note: Fill nail holes, cracks and other defects with Cabot's Wood Tone Putty after applying the first coat of this product for accurate colour matching. Remove stains, dirt, wax, grease and oil with mineral turpentine. Remove any polish with a suitable floor polish remover. <p>BARE TIMBER Sand the surface smooth using 180 - 240 grit sandpaper. Sand only in the direction of the grain. Remove all traces of sanding dust.</p> <p>PREVIOUSLY COATED TIMBER Completely remove the previous coating using a paint stripper or by sanding. Remove all traces of sanding dust.</p>
Application Procedure And Equipment	<ul style="list-style-type: none"> Stir thoroughly with a broad flat paddle until pigment is mixed in and colour is uniform. Keep well stirred during use. If using more than one can, mix all cans together into a larger container to ensure colour uniformity. Apply with a good quality brush or roller. Apply three coats depending on the required depth of colour, allowing 2 hours between coats. For best results, sand between coats using 240 grit sandpaper. <p>COLOUR STRENGTH If the desired colour is achieved after 1 or 2 coats of Cabot's Stain & Varnish Water Based, use Cabot's Cabothane Clear Water Based to complete the 3 coat system.</p> <p>MAINTENANCE Regular inspection of all coated surfaces is recommended. Re-coating is recommended when the coating looks dull or tired. Clean with Cabot's Floor Clean following label instructions. Sand with 240 grit sandpaper then apply 1-2 coats.</p> <p>STAINING A FLOOR The natural colour of the timber will affect the finished colour of the stain. Always test the stain on an off cut or concealed part of the actual job before proceeding. Follow preparation steps above. Stain first with one coat of Cabot's Stain & Varnish Water Based using a 6 - 10mm nap roller. Additional coats can be applied if a deeper colour is required. Topcoat with Cabot's CFP Floor Water Based following label instructions.</p>

Health And Safety

MSDS Number	14282701	Using Safety Precautions	RISK: Irritating to eyes and skin. Avoid contact with skin and eyes. Use only in well ventilated areas. If using indoors keep windows and doors open during use and while drying.
Health Effects	<p>If poisoning occurs, contact a doctor or Poisons Information Centre AUST 131 126, NZ 0800 764 766.</p> <p>SWALLOWED: If swallowed, give plenty of water to drink. Seek medical advice.</p> <p>EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.</p> <p>For further information or a copy of the Product SafetyData Sheet telephone Cabot's Customer Service Department on AUST 1800 011 006, NZ 0800222 687.</p> <p>For emergencies phone AUST 1800 033 111, NZ 0800 734 607.</p>	Flammability	This product is non-flammable.
Storage	Keep out of reach of children.	Disposal	Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.
In the case of emergency, please call 1800 033 111			

Transport And Storage

Pack A	538-line
Size 1L 500ml 250ml	Weight 1.2Kg 0.61Kg 0.33Kg

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427