

## Feast Watson Timber Floor Stain & Varnish Liming White

**AU\_DW02892**

Part A	710W0053
--------	----------

### Description

FEAST WATSON TIMBER FLOOR STAIN & VARNISH LIMING WHITE IS A WATER BASED, INTERIOR FLOOR FINISH WHICH GIVES A SOFT, MILKY WHITE EFFECT TO ALL INTERIOR TIMBER FLOORING. TIMBER FLOOR STAIN & VARNISH LIMING WHITE IS A SEMI-TRANSPARENT COATING THAT ALLOWS THE GRAIN PATTERN OF TIMBER TO REMAIN VISIBLE. ONE COAT GIVES A SUBTLE, PALE COLOUR; MULTIPLE COATS WILL BUILD THE OPACITY AND WHITENESS.

### Features

- GIVES A SOFT, MILKY WHITE EFFECT
- GRAIN PATTERN OF TIMBER REMAINS VISIBLE

### Uses

SUITABLE FOR ALL INTERIOR TIMBER FLOORING.





### Precautions And Limitations

Do NOT apply this product at temperatures below 10°C or above 35°C.

### Performance Guide

Weather	Interior only	Abrasion	Good
---------	---------------	----------	------

### Typical Properties

Gloss Level	20-30% measured at 60 degrees	Thinner	Water																								
Clean Up	 Water																										
Application Method	 Brush  Roller  Pad																										
Application Conditions	<table> <tr> <td><b>Solids By Volume</b></td><td>26</td><td></td><td></td></tr> <tr> <td></td><td><b>Min</b></td><td><b>Max</b></td><td><b>Recommended</b></td></tr> <tr> <td><b>Wet Film Per Coat (microns)</b></td><td></td><td></td><td></td></tr> <tr> <td><b>Dry Film Per Coat (microns)</b></td><td></td><td></td><td></td></tr> <tr> <td><b>Recoat Time (min)</b></td><td>2 hours</td><td></td><td></td></tr> <tr> <td><b>Theoretical Spread Rate (m<sup>2</sup>/L)</b></td><td></td><td></td><td></td></tr> </table>			<b>Solids By Volume</b>	26				<b>Min</b>	<b>Max</b>	<b>Recommended</b>	<b>Wet Film Per Coat (microns)</b>				<b>Dry Film Per Coat (microns)</b>				<b>Recoat Time (min)</b>	2 hours			<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>			
<b>Solids By Volume</b>	26																										
	<b>Min</b>	<b>Max</b>	<b>Recommended</b>																								
<b>Wet Film Per Coat (microns)</b>																											
<b>Dry Film Per Coat (microns)</b>																											
<b>Recoat Time (min)</b>	2 hours																										
<b>Theoretical Spread Rate (m<sup>2</sup>/L)</b>																											
Typical Properties Notes	<p><b>COVERAGE</b>                      Softwood: 8 - 10m<sup>2</sup> per litre.                      Hardwood: 10 - 12m<sup>2</sup> per litre.                      Cork: 8 - 10m<sup>2</sup> per litre.</p> <p><b>DRYING TIME</b>                      Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.                      Touch Dry: 30 minutes.                      Recoat: 2 hours.                      Allow 24 hours before light foot traffic and 72 hours for normal foot traffic. Full curing after 7 days.                      Wait until fully cured to replace furniture and rugs. All furniture should have protective felt pads on floor contact points. Do not use furnishing with rubber pads or backing.</p>																										

## Application Guide

<b>Surface Preparation</b>	<ul style="list-style-type: none"> <li>NEW OR BARE TIMBER/CORK Punch exposed nails below the surface. Holes and imperfections should be filled with timber putty. Sand timber to an even, smooth surface. Vacuum and wipe to remove dust. Prepare uncoated cork tiles in accordance with the supplier's recommendation. Seal bare timber with 1 coat of Feast Watson PROOFSEAL. Apply according to label instructions.</li> </ul> <p>PREVIOUSLY COATED TIMBER Previously coated surfaces need to be sanded back to bare timber or cork. Remove all sanding dust before coating.</p>
<b>Application Procedure And Equipment</b>	<ul style="list-style-type: none"> <li>Stir TIMBER FLOOR STAIN &amp; VARNISH LIMING WHITE thoroughly before and during use with a flat blade stirrer, being careful not to introduce bubbles. If using more than one can of the same colour to complete a job, combine both cans and stir thoroughly. Test colour on an off-cut or inconspicuous area prior to coating the whole job to ensure satisfaction with colour choice. Apply with a Feast Watson® FLOOR FINISH APPLICATOR, brush or short nap roller. Work along the whole length of 3 - 4 floorboards at a time, maintaining a wet edge to prevent lap marks and lay off in the direction of the grain. Take care to not introduce bubbles. This is a three coat flooring system. If the desired colour is achieved in less than three coats, complete the system with a suitable water based floor coating, such as Cabot's® CFP as per label instructions. Stronger colour can be developed with further coats of TIMBER FLOOR STAIN &amp; VARNISH LIMING WHITE. Continue applying coats by the above procedure until the desired colour is achieved. Multiple coats will build colour depth.</li> </ul> <p>Do NOT apply this product at temperatures below 10°C or above 35°C.</p> <p>THINNING In hot temperatures (over 30°C) thin with up to 100mls of water per litre to ease application and slow drying.</p> <p>MAINTENANCE Regularly clean using FLOORCLEAN. Monitor the surface for signs of colour loss or surface defects. When floor requires an additional coat of TIMBER FLOOR STAIN &amp; VARNISH LIMING WHITE, apply as per above procedure.</p>

### Health And Safety

<b>MSDS Number</b>	DLXGHSEN000258	<b>Using Safety Precautions</b>	Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapour or spray. Wear overalls, safety shoes, impervious gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Keep containers closed when not in use.
<b>Health Effects</b>	<p><b>FIRST AID:</b> If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand.</p> <p><b>SWALLOWED:</b> If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.</p> <p><b>EYE:</b> If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p><b>SKIN:</b> If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice.</p> <p><b>INHALED:</b> Remove from contaminated area. Seek medical advice.</p>	<b>Flammability</b>	Non-flammable liquid.
<b>Fire Suppression</b>	If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).	<b>Protective Equipment</b>	Wear overalls, safety shoes, impervious gloves and safety glasses.
<b>Storage</b>	Keep containers closed when not in use.	<b>Other</b>	<p>SEE THE SAFETY DATA SHEET FOR ADDITIONAL INFORMATION.</p> <p>IN A TRANSPORT EMERGENCY DIAL 000 POLICE OR FIRE BRIGADE.</p> <p>For further information or a copy of the Safety Data Sheet call Feast Watson® Customer Service Department on AUST 1800 252 502, NZ 0800 222 687.</p> <p>EMERGENCY INFORMATION: AUST – 1800 220 770; NZ – 0800 220 770 (ALL HOURS).</p>

**In the case of emergency, please call 1800 033 111**

### Transport And Storage

<b>Pack A</b>	710W0053
<b>Size</b> 4L	<b>Weight</b> 4.61kg

#### Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427